

NetWitness[®] Platform XDR

Version 12.1.0.0

API Guide

Contact Information

NetWitness Community at <https://community.netwitness.com> contains a knowledge base that answers common questions and provides solutions to known problems, product documentation, community discussions, and case management.

Trademarks

RSA and other trademarks are trademarks of RSA Security LLC or its affiliates ("RSA"). For a list of RSA trademarks, go to <https://www.rsa.com/en-us/company/rsa-trademarks>. Other trademarks are trademarks of their respective owners.

License Agreement

This software and the associated documentation are proprietary and confidential to RSA Security LLC or its affiliates and are furnished under license, and may be used and copied only in accordance with the terms of such license and with the inclusion of the copyright notice below. This software and the documentation, and any copies thereof, may not be provided or otherwise made available to any other person.

No title to or ownership of the software or documentation or any intellectual property rights thereto is hereby transferred. Any unauthorized use or reproduction of this software and the documentation may be subject to civil and/or criminal liability.

This software is subject to change without notice and should not be construed as a commitment by RSA.

Third-Party Licenses

This product may include software developed by parties other than RSA. The text of the license agreements applicable to third-party software in this product may be viewed on the product documentation page on NetWitness Community. By using this product, a user of this product agrees to be fully bound by terms of the license agreements.

Note on Encryption Technologies

This product may contain encryption technology. Many countries prohibit or restrict the use, import, or export of encryption technologies, and current use, import, and export regulations should be followed when using, importing or exporting this product.

Distribution

Use, copying, and distribution of any RSA Security LLC or its affiliates ("RSA") software described in this publication requires an applicable software license.

RSA believes the information in this publication is accurate as of its publication date. The information is subject to change without notice.

THE INFORMATION IN THIS PUBLICATION IS PROVIDED "AS IS." RSA MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WITH RESPECT TO THE INFORMATION IN THIS PUBLICATION, AND SPECIFICALLY DISCLAIMS IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

© 2020 RSA Security LLC or its affiliates. All Rights Reserved.

October, 2022

Table of Contents

Overview	2
Current Version	2
Schema	2
HTTP Usage	2
Case Sensitive	3
Error Response	3
Pagination	4
Authentication and Authorization	5
Obtaining a Token	5
Using a Username and Password	5
Using a Refresh Token	6
Authorization	8
Incident APIs	9
Attributes	9
Incident Priority	10
Incident Status	11
Milestone	11
Requests	11
Get a Single Incident	11
Get Incidents by Date Range	13
Update an Incident	15
Remove an Incident	17
Add a Journal Entry	18
Get an Incident's Alerts	19
Persisting events in an alert	23
Suspending persist of events in an alert	24
Persisting events in an incident	24
Suspending persist of events in an incident	25
Get Incident history	26
Get Incident Stats	27
Get Incident User Stats	29
Services Information	30
Get Service IDs of all Services	30
Sample Request	30
Sample Response	30
Get List of Service IDs by Service Name	31
Sample Request	31
Sample Response	31

Endpoint APIs	33
Get Hosts	33
Sample Request	34
Sample Response	34
Get Hosts with Filter	35
Sample Request	35
HTTP request	36
Sample Response	36
Get List of Snapshots for Host	38
Sample Request	38
Sample Response	38
Get Snapshot Details for the Host	38
Response Fields	38
Sample Request	46
Sample Response	46
Get Files	48
Sample Request	51
Sample Response	51
Request Scan	52
Path Parameters	52
Request Parameters	53
Sample Request	53
Sample Response	53
Request Scan with given CPU Usage	53
Path Parameters	53
Request Parameters	53
Sample Request	54
Sample Response	54
Request Stop Scan	54
Path Parameters	54
Request Parameters	54
Sample Request	54
Sample Response	54
Get Alerts for a Host	55
Sample Request	55
Sample Response	55
Get Alerts for a File	56
Sample Request	57
Sample Response	57
Request File Download to Server	58
Path Parameters	58

Request Parameters	59
Sample Request	59
HTTP request	59
Sample Response	59
Request Multiple File Downloads to Server	59
Path Parameters	60
Request Parameters	60
Sample Request	60
HTTP request	60
Sample Response	60
Request MFT Download	61
Path Parameters	61
Request Parameters	61
Sample Request	61
Sample Response	61
Request System Dump Download	62
Path Parameters	62
Request Parameters	62
Sample Request	62
Sample Response	62
Request Process Dump Download	63
Path Parameters	63
Sample Request	63
Sample Response	63
Request Network Isolation	63
Path Parameters	64
Request Parameters	64
Sample Request	64
HTTP request	64
Sample Response	64
Update Network Isolation Exclusion List	65
Path Parameters	65
Request Parameters	65
Sample Request	65
HTTP request	65
Sample Response	65
Release from Network Isolation	66
Path Parameters	66
Request Parameters	66
Sample Request	66
HTTP request	66

Overview

The NetWitness Platform API can be accessed using the same host and port as the NetWitness user interface.

Current Version

By default, all requests to the REST API will automatically use the latest version of the API available. To provide API stability, clients can specify the API version to use by adding the `NetWitness-Version` HTTP header:

```
NetWitness-Version: 1.0
```

Schema

All data is sent and received as JSON. Any resources containing fields without values will have those fields included with `null` as the value instead of being omitted.

Any fields containing timestamps or dates will be in [ISO 8601](#) format:

```
YYYY-MM-DDTHH:MM:SS.SSSZ
```

HTTP Usage

The RSA NetWitness API tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP verbs and status codes.

HTTP Verbs

Verb	Usage
<code>GET</code>	Used to retrieve a resource.
<code>POST</code>	Used to create a new resource.
<code>PATCH</code>	Used to update an existing resource, including partial updates. Only fields that are modified should be included in the request.
<code>PUT</code>	Used to replace an existing resource.
<code>DELETE</code>	Used to delete an existing resource.

HTTP Status Codes

Status code	Usage
<code>200 OK</code>	The request completed successfully.

201 Created	A new resource has been created successfully. The resource's URI is available from the response's <code>Location</code> header.
204 No Content	An update to an existing resource has been applied successfully.
400 Bad Request	The request was malformed. The response body will include an error providing further information. See Error Response .
401 Unauthorized	Similar to <code>403 Forbidden</code> , but specifically for use when authentication is required and has failed or has not yet been provided. See Authentication and Authorization .
403 Forbidden	The request was valid, but the server is refusing the action. The user might not have the necessary permissions for a resource.
404 Not Found	The requested resource does not exist.
500 Internal Server Error	An unexpected error has occurred. The response body will include a message providing further information.

Case Sensitive

All URLs, request parameters and JSON fields are case sensitive.

Error Response

A common JSON structure is always returned for errors:

Path	Type	Description
<code>status</code>	Number	The HTTP status code returned.
<code>timestamp</code>	String	The timestamp of the request.
<code>errors[]</code>	Array	An array of errors for the given request.
<code>errors[].message</code>	String	A user-friendly error message explaining what went wrong.
<code>errors[].field</code>	String	The field or parameter containing the error.

```
{
  "status" : 400,
  "timestamp" : "2022-12-12T09:10:36.642447Z",
  "errors" : [ {
    "message" : "Value must be less than or equal to \"10\"",
    "field" : "start"
  }, {
    "message" : "Invalid range"
  } ]
}
```


Pagination

A common JSON structure is always used for paginated results:

Path	Type	Description
items	Array	An array containing the requested resources.
pageNumber	Number	The requested page number.
pageSize	Number	The requested number of items to return in a single page.
totalPages	Number	The total number of pages available.
totalItems	Number	The total number of items available.
hasNext	Boolean	Indicates if there is a page containing results after this page.
hasPrevious	Boolean	Indicates if there is a page containing results before this page.

```
{
  "items" : [ ],
  "pageNumber" : 0,
  "pageSize" : 10,
  "totalPages" : 3,
  "totalItems" : 25,
  "hasNext" : true,
  "hasPrevious" : false
}
```

Authentication and Authorization

All requests must include the **NetWitness-Token** HTTP header containing a valid JSON Web Token (JWT):

```
NetWitness-Token:
eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHAiOjE1MTEyNDczODYyNjMsImZlcyI6InNlY3VyaXR5LXNlcnZlciozODA1NTA0OS0xZWMyLTQ0MDAtOTUwYS0zZTVkMmJiYTljMjIiLCJpYXQiOjE1MTEyMTEzODYyNjMsImF1dGhvcmI0aWVzIjpbIkFkbWluaXN0cmF0b3JzIl0sInVzZXJfbmFtZSI6ImFkbWluIn0.StBjg9ruIX4FryfCX8qvrSBGZHF8DN3qHZM0Ei9-thFndm1q_DLP_cnh8Fpm43fdKcs1ErcVRTqhaYvVULYmsF9ShUaSThpLts6zbJVEKlq3ldUGWWCY9bfVGRH3n5KmWzITPi7xZ-Rf_Kp2Sj8ecVAip3qDwha7TxYrReXefCnUj0UxgaaXjeZIFjwxFmK6NPZ7TAK90cvcVhozaR8V92g1kUVP8_54x7iZ2jL4JvDPaScWBjBTvVEffHNbX9_iLNoRmKqvDELs1a6E_trkSREogCt6pZh709Qh70uoC3BsKwNQKbHNEOU1tRPFaUFfRH7bCdp8v3Aeh3PTaKEuQA
```

The JSON Web Token is defined in [RFC-7519](#). Tokens can be obtained using the methods outlined below.

In the remainder of this document, the token will be truncated to just **eyJ...AT** for brevity.

Obtaining a Token

A JSON Web Token can be obtained using the methods below.

Using a Username and Password

Users can retrieve an access token using their username and password credentials. Since the API gateway is secured using TLS, all credentials will be encrypted in transit.

```
POST /rest/api/auth/userpass
```

Request Parameters

Parameter	Description
username	The username of the account to authenticate.
password	The password of the account.

Response Fields

Path	Type	Description
id	String	The account identifier.
roles	Array	The roles assigned to the user.

Path	Type	Description
<code>accessToken</code>	String	A digitally signed access token that is acceptable as proof of authentication at any Launch service that trusts the public key of this service. The string holds a JSON web-token. See RFC-7519 .
<code>refreshToken</code>	String	A digitally signed refresh token that can be used to refresh an expired access token. Refresh tokens have longer expiry periods and can be used by services to re-authenticate users without (storing and) presenting credentials.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/auth/userpass' -i -X POST \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/x-www-form-urlencoded; charset=ISO-8859-1' \
  -d 'username=ian&password=changeMe'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:14:33 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 106
```

```
{
  "id" : "ian",
  "roles" : [ "Analyst" ],
  "accessToken" : "eyJ...AT",
  "refreshToken" : "eyJ...AT"
}
```

Using a Refresh Token

Users can also retrieve an access token using a refresh token.

```
POST /rest/api/auth/token
```

Request Parameters

Parameter	Description
token	A refresh token.

Response Fields

Path	Type	Description
id	String	The account identifier.
roles	Array	The roles assigned to the user.
accessToken	String	A digitally signed access token that is acceptable as proof of authentication at any Launch service that trusts the public key of this service. The string holds a JSON web-token. See RFC-7519 .
refreshToken	String	A digitally signed refresh token that can be used to refresh an expired access token. Refresh tokens have longer expiry periods and can be used by services to re-authenticate users without (storing and) presenting credentials.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/auth/token' -i -X POST \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/x-www-form-urlencoded; charset=ISO-8859-1' \
  -d
'token=eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHAiOjE2NzM0Mjg0NzMyNzEsImZcyI6InNlY3VyaXR5LXNlcnZlc2giOnRydWUsInVzZXJfcmFtZSI6Im1hbiJ9.on50Pmw09pw5HTqVZN3FkAkYm6urCzCCPeHIRDFN20L1WHUklb_YzkTls9sf_8jleZ8jJb1R6avffEBBBthE8Livw0Nt-7iWatG7IHm_oijB2EookKXRbxv9461VssfXWdbY7zs-s51tI96atQYbQPfOmPoGogPW_bzZJgFcEAbRBydaVYktKR0t01xIU0PKabBo_GBwutYt0054K1jiz0hiL_2qABm7WrjjLuL0nscLCIZyN64DdYtWaE30NhRyvrvjKsnlkCec5ucFX0joRK03cocqFJuCyoM-TKSbBpjUDJh2c0jP1wP17d0R-KQYrvbNSaqRef2_KyBbT6Bm0cg'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:14:33 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 106
```

```
{
  "id" : "ian",
  "roles" : [ "Analyst" ],
  "accessToken" : "eyJ...AT",
  "refreshToken" : "eyJ...AT"
}
```

Authorization

In order to make requests through the NetWitness Platform API, users must belong to roles that have the `integration-server.api.access` permission, as well as any underlying permissions required to fulfill the request.

Incident APIs

An Incident is a logically grouped set of alerts created automatically by the Incident Aggregation Engine and grouped by a specific criteria. An Incident, available in the Respond Interface, allows an Analyst to triage, investigate, and remediate these groups of alerts. Incidents can be moved between users, notated, and explored via the nodal graph. Incidents allow users to ensure they understand the full scope of an attack or event in their NW system and then take action.

Attributes

The incident resource is comprised of the following attributes:

Path	Type	Description
<code>id</code>	String	The unique identifier of the incident.
<code>title</code>	String	The title of the incident.
<code>summary</code>	String	The summary of the incident.
<code>priority</code>	String	The incident priority. See the valid values .
<code>riskScore</code>	Number	The incident risk score is calculated based on the associated alert's risk score. Risk score ranges from 0 (no risk) to 100 (highest risk).
<code>status</code>	String	The current status. See the valid values .
<code>alertCount</code>	Number	The number of alerts associated with an incident.
<code>averageAlertRiskScore</code>	Number	The average risk score of the alerts associated with the incident. Risk score ranges from 0 (no risk) to 100 (highest risk).
<code>sealed</code>	Boolean	Indicates if additional alerts can be associated with an incident. A <code>sealed</code> incident cannot be associated with additional alerts.
<code>totalRemediationTaskCount</code>	Number	The number of total remediation tasks for an incident.
<code>openRemediationTaskCount</code>	Number	The number of open remediation tasks for an incident.
<code>created</code>	String	The timestamp of when the incident is created.
<code>lastUpdated</code>	String	The timestamp of when the incident was last updated.
<code>lastUpdatedBy</code>	String	The NetWitness user identifier of the user who last updated the incident.
<code>assignee</code>	String	The NetWitness user identifier of the user currently working on the incident.
<code>sources</code>	Array	Unique set of sources for all of the alerts in an incident.

Path	Type	Description
<code>ruleId</code>	String	The unique identifier of the rule that created the incident.
<code>firstAlertTime</code>	String	The timestamp of the earliest occurring Alert in this incident.
<code>categories</code>	Array	The list of categories this incident is categorized under.
<code>categories[].id</code>	String	The unique category identifier.
<code>categories[].parent</code>	String	The parent name of the category.
<code>categories[].name</code>	String	The friendly name of the category.
<code>journalEntries</code>	Array	Set of notes about the incident investigation, also known as the JournalEntry.
<code>journalEntries[].id</code>	String	The unique journal entry identifier.
<code>journalEntries[].author</code>	String	The author of this entry.
<code>journalEntries[].notes</code>	String	Notes and observations about the incident.
<code>journalEntries[].created</code>	String	The timestamp of the journal entry created date.
<code>journalEntries[].lastUpdated</code>	String	The timestamp of the journal entry last updated date.
<code>journalEntries[].milestone</code>	String	Incident milestone classifier. See the valid values .
<code>createdBy</code>	String	The NetWitness user id or name of the rule that created the incident.
<code>deletedAlertCount</code>	Number	The number of alerts that are deleted from the incident.
<code>eventCount</code>	Number	The number of events associated with incident.
<code>alertMeta</code>	String	An object containing unique set of meta values, by type, across all alerts associated with this incident.
<code>alertMeta.SourceIp</code>	Array	Unique source IP addresses.
<code>alertMeta.DestinationIp</code>	Array	Unique destination IP addresses.

Incident Priority

The `priority` field can contain these values:

Value	Description
<code>Low</code>	Low Priority
<code>Medium</code>	Medium Priority
<code>High</code>	High Priority
<code>Critical</code>	Critical

Incident Status

The `status` field can contain these values:

Value	Description
<code>New</code>	New incident.
<code>Assigned</code>	Incident is assigned to a user.
<code>InProgress</code>	Incident response is in progress.
<code>RemediationRequested</code>	Remediation tasks have been requested.
<code>RemediationComplete</code>	Remediation tasks are complete.
<code>Closed</code>	Incident is closed.
<code>ClosedFalsePositive</code>	Incident is closed as it was created due to false positive.

Milestone

Each journal entry can contain a `milestone` consisting of these values:

Value	Description
<code>Reconnaissance</code>	Intruder is in the initial phase of the attack where targets and vulnerabilities are identified.
<code>Delivery</code>	Intruder transmitted malware to the target.
<code>Exploitation</code>	Malware code triggers, which takes action on target network to exploit vulnerability.
<code>Installation</code>	Malware weapon installs access point usable by intruder.
<code>CommandAndControl</code>	Malware enables intruder to have persistent access to target network.
<code>ActionOnObjective</code>	Intruder takes action to achieve their goals, such as data exfiltration, data destruction, or encryption for ransom.
<code>Containment</code>	Incident is contained.
<code>Eradication</code>	Necessary actions taken to eliminate components of incident and restore the system status.
<code>Closure</code>	Incident is addressed.

Requests

Get a Single Incident

A single incident can be retrieved using an incident's unique identifier.

```
GET /rest/api/incidents/{id}
```


Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/INC-100' -i -X GET \  
-H 'Accept: application/json;charset=UTF-8' \  
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Transfer-Encoding: chunked  
Date: Mon, 12 Dec 2022 09:15:50 GMT  
Keep-Alive: timeout=60  
Connection: keep-alive  
Content-Length: 1329
```

```

{
  "id" : "INC-100",
  "title" : "Suspected C&C with suspicious-domain.com",
  "summary" : "Security Analytics detected communications with suspicious-domain.com
that may be command and control malware.",
  "priority" : "Critical",
  "riskScore" : 100,
  "status" : "InProgress",
  "alertCount" : 1,
  "averageAlertRiskScore" : 100,
  "sealed" : true,
  "totalRemediationTaskCount" : 4,
  "openRemediationTaskCount" : 5,
  "created" : "2018-01-01T04:49:27.870Z",
  "lastUpdated" : "2022-12-12T09:15:49.787Z",
  "lastUpdatedBy" : "duke",
  "assignee" : "ian",
  "sources" : [ "Malware Analysis" ],
  "ruleId" : "55e49a79e4b01a1d2be502bc",
  "firstAlertTime" : "2017-08-04T16:49:22Z",
  "categories" : [ {
    "id" : "55e49a79e4b01a1d2be5022e",
    "parent" : "Malware",
    "name" : "Password dumper"
  }, {
    "id" : "55e49a79e4b01a1d2be50228",
    "parent" : "Hacking",
    "name" : "Path traversal"
  } ],
  "journalEntries" : [ {
    "id" : "20",
    "author" : "admin",
    "notes" : "Updated status",
    "created" : "2017-11-15T20:20:54.785Z",
    "lastUpdated" : "2017-11-15T20:20:54.785Z",
    "milestone" : "Containment"
  } ],
  "createdBy" : "norm",
  "deletedAlertCount" : 100,
  "eventCount" : 0,
  "alertMeta" : {
    "SourceIp" : [ "10.11.12.345" ],
    "DestinationIp" : [ "11.11.11.111", "11.22.33.444" ]
  }
}

```

Get Incidents by Date Range

Incidents can be retrieved by the date and time they were created.

```
GET /rest/api/incidents
```

The requested date range can be unbounded, by only supplying either the `since` or `until` parameter, or bounded, by providing both parameters.

Request Parameters

Parameter	Description
<code>pageNumber</code>	The requested page number.
<code>pageSize</code>	The maximum number of items to return in a single page.
<code>since</code>	A timestamp in ISO 8601 format (e.g., <code>2018-01-01T14:00:00.000Z</code>). Retrieve incidents created on and after this timestamp.
<code>until</code>	A timestamp in ISO 8601 format (e.g., <code>2018-01-01T14:00:00.000Z</code>). Retrieve incidents created on and before this timestamp.

All results will be returned using the [paginated response payload](#) sorted by the `created` date, in descending order.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents?since=2018-01-01T04%3A00%3A00.000Z&until=2018-01-01T05%3A00%3A00.000Z&pageSize=100&pageNumber=0' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:47 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 1560
```

```
{
  "items" : [ {
    "id" : "INC-100",
    "title" : "Suspected C&C with suspicious-domain.com",
    "summary" : "Security Analytics detected communications with suspicious-domain.com that may be command and control malware.",
    "priority" : "Critical",
    "riskScore" : 100,
    "status" : "Assigned",
```

```

"alertCount" : 1,
"averageAlertRiskScore" : 100,
"sealed" : true,
"totalRemediationTaskCount" : 4,
"openRemediationTaskCount" : 5,
"created" : "2018-01-01T04:49:27.870Z",
"lastUpdated" : "2017-08-04T16:49:27.870Z",
"lastUpdatedBy" : "norm",
"assignee" : "tony",
"sources" : [ "Malware Analysis" ],
"ruleId" : "55e49a79e4b01a1d2be502bc",
"firstAlertTime" : "2017-08-04T16:49:22Z",
"categories" : [ {
  "id" : "55e49a79e4b01a1d2be5022e",
  "parent" : "Malware",
  "name" : "Password dumper"
}, {
  "id" : "55e49a79e4b01a1d2be50228",
  "parent" : "Hacking",
  "name" : "Path traversal"
} ],
"journalEntries" : [ {
  "id" : "20",
  "author" : "admin",
  "notes" : "Updated status",
  "created" : "2017-11-15T20:20:54.785Z",
  "lastUpdated" : "2017-11-15T20:20:54.785Z",
  "milestone" : "Containment"
} ],
"createdBy" : "norm",
"deletedAlertCount" : 100,
"eventCount" : 0,
"alertMeta" : {
  "SourceIp" : [ "10.11.12.345" ],
  "DestinationIp" : [ "11.11.11.111", "11.22.33.444" ]
}
} ],
"pageNumber" : 0,
"pageSize" : 100,
"totalPages" : 1,
"totalItems" : 1,
"hasNext" : false,
"hasPrevious" : false
}

```

Update an Incident

Currently an incident's **status** and **assignee** can be modified using the incidents endpoint.

```
PATCH /rest/api/incidents/{id}
```

The **assignee** field must include the unique identifier for a valid NetWitness user. The list of users can be found in the security section of the administration user interface.

Request Fields

Path	Type	Description
status	String	The current status. See the valid values .
assignee	String	The NetWitness user identifier of the user currently working on the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/INC-100' -i -X PATCH \  
-H 'NetWitness-Token: eyJ...AT' \  
-H 'Accept: application/json; charset=UTF-8' \  
-H 'Content-Type: application/json; charset=UTF-8' \  
-d '{"status": "InProgress"}'
```

Sample Response

```
HTTP/1.1 200 OK  
Content-Type: application/json; charset=UTF-8  
Transfer-Encoding: chunked  
Date: Mon, 12 Dec 2022 09:15:49 GMT  
Keep-Alive: timeout=60  
Connection: keep-alive  
Content-Length: 1330
```

```

{
  "id" : "INC-100",
  "title" : "Suspected C&C with suspicious-domain.com",
  "summary" : "Security Analytics detected communications with suspicious-domain.com
that may be command and control malware.",
  "priority" : "Critical",
  "riskScore" : 100,
  "status" : "InProgress",
  "alertCount" : 1,
  "averageAlertRiskScore" : 100,
  "sealed" : true,
  "totalRemediationTaskCount" : 4,
  "openRemediationTaskCount" : 5,
  "created" : "2018-01-01T04:49:27.870Z",
  "lastUpdated" : "2022-12-12T09:15:49.153Z",
  "lastUpdatedBy" : "duke",
  "assignee" : "tony",
  "sources" : [ "Malware Analysis" ],
  "ruleId" : "55e49a79e4b01a1d2be502bc",
  "firstAlertTime" : "2017-08-04T16:49:22Z",
  "categories" : [ {
    "id" : "55e49a79e4b01a1d2be5022e",
    "parent" : "Malware",
    "name" : "Password dumper"
  }, {
    "id" : "55e49a79e4b01a1d2be50228",
    "parent" : "Hacking",
    "name" : "Path traversal"
  } ],
  "journalEntries" : [ {
    "id" : "20",
    "author" : "admin",
    "notes" : "Updated status",
    "created" : "2017-11-15T20:20:54.785Z",
    "lastUpdated" : "2017-11-15T20:20:54.785Z",
    "milestone" : "Containment"
  } ],
  "createdBy" : "norm",
  "deletedAlertCount" : 100,
  "eventCount" : 0,
  "alertMeta" : {
    "SourceIp" : [ "10.11.12.345" ],
    "DestinationIp" : [ "11.11.11.111", "11.22.33.444" ]
  }
}

```

Remove an Incident

A single incident can be removed using the incident's unique identifier.

```
DELETE /rest/api/incidents/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/INC-100' -i -X DELETE \  
-H 'Accept: application/json;charset=UTF-8' \  
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 204 No Content  
Date: Mon, 12 Dec 2022 09:15:51 GMT  
Keep-Alive: timeout=60  
Connection: keep-alive
```

Add a Journal Entry

A journal entry, or note, can be added to an existing incident.

```
POST /rest/api/incidents/{id}/journal
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Request Fields

Path	Type	Description
<code>author</code>	<code>String</code>	The NetWitness user id of the user creating the journal entry.
<code>notes</code>	<code>String</code>	Notes and observations about the incident.
<code>milestone</code>	<code>String</code>	The incident milestone classifier.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/INC-100/journal' -i -X POST \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Accept: application/json; charset=UTF-8' \
-H 'Content-Type: application/json; charset=UTF-8' \
-d '{"author": "duke", "notes": "This incident is contained.", "milestone": "Containment"}'
```

Sample Response

```
HTTP/1.1 201 Created
Location: https://api.netwitness.local/rest/api/incidents/INC-100
Date: Mon, 12 Dec 2022 09:15:51 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Get an Incident's Alerts

All the alerts that are associated with an incident can be retrieved using the incident's unique identifier.

```
GET /rest/api/incidents/{id}/alerts
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Request Parameters

Parameter	Description
<code>pageNumber</code>	The requested page number.
<code>pageSize</code>	The maximum number of items to return in a single page.

Response Fields

Path	Type	Description
<code>items</code>	Array	An array containing the requested resources.
<code>pageNumber</code>	Number	The requested page number.

Path	Type	Description
pageSize	Number	The requested number of items to return in a single page.
totalPages	Number	The total number of pages available.
totalItems	Number	The total number of items available.
hasNext	Boolean	Indicates if there is a page containing results after this page.
hasPrevious	Boolean	Indicates if there is a page containing results before this page.
items[].id	String	The unique alert identifier.
items[].title	String	The title or name of the rule that created the alert.
items[].detail	String	The details of the alert. This can be the module name or meta that the module included.
items[].created	String	The timestamp of the alert created date.
items[].source	String	The source of this alert. For example, "Event Stream Analysis", "Malware Analysis", etc.
items[].riskScore	Number	The risk score of this alert, usually in the range 0 - 100.
items[].type	String	The type of alert, "Network", "Log", etc.
items[].events	Array	The events that make up this alert.
items[].events[].source	Object	The source of the event.
items[].events[].source.device	Object	The device contains the endpoint network information.
items[].events[].source.device.ipAddress	String	The IP address.
items[].events[].source.device.port	Number	The port.
items[].events[].source.device.macAddress	String	The ethernet MAC address.
items[].events[].source.device.dnsHostname	String	The DNS resolved hostname.
items[].events[].source.device.dnsDomain	String	The top-level domain from the DNS resolved hostname.
items[].events[].source.user	Object	The user contains the endpoint user information.
items[].events[].source.user.userName	String	The unique username.
items[].events[].source.user.emailAddress	String	An email address.
items[].events[].source.user.adUsername	String	An Active Directory (AD) username.
items[].events[].source.user.adDomain	String	An Active Directory (AD) domain.

Path	Type	Description
<code>items[].events[].destination</code>	Object	The destination of the event.
<code>items[].events[].destination.device</code>	Object	The device contains the endpoint network information.
<code>items[].events[].destination.device.ipAddress</code>	String	The IP address.
<code>items[].events[].destination.device.port</code>	Number	The port.
<code>items[].events[].destination.device.macAddress</code>	String	The ethernet MAC address.
<code>items[].events[].destination.device.dnsHostname</code>	String	The DNS resolved hostname.
<code>items[].events[].destination.device.dnsDomain</code>	String	The top-level domain from the DNS resolved hostname.
<code>items[].events[].destination.user</code>	Object	The user contains the endpoint user information.
<code>items[].events[].destination.user.username</code>	String	The unique username.
<code>items[].events[].destination.user.emailAddress</code>	String	An email address.
<code>items[].events[].destination.user.adUsername</code>	String	An Active Directory (AD) username.
<code>items[].events[].destination.user.adDomain</code>	String	An Active Directory (AD) domain.
<code>items[].events[].domain</code>	String	The top-level domain or Windows domain.
<code>items[].events[].eventSource</code>	String	The source of the event. This may be a fully-qualified hostname with a port, or simple name.
<code>items[].events[].eventSourceId</code>	String	The unique identifier of the event on the source. For Network and Log events, this is the Nextgen Session ID.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/INC-100/alerts?pageSize=10&pageNumber=0' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:51 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 1301
```

```
{
  "items" : [ {
    "id" : "5a6b81639491573f1e73676c",
    "title" : "LogOn Rule",
    "detail" : "Module_5a5cddb3e4b0ac40016df562_Alert",
    "created" : "2018-01-26T19:28:35Z",
    "source" : "Event Stream Analysis",
    "riskScore" : 90,
    "type" : "Network",
    "events" : [ {
      "source" : {
        "device" : {
          "ipAddress" : "58.229.117.56",
          "port" : 57429,
          "macAddress" : "00:13:c3:3b:c7:00",
          "dnsHostname" : null,
          "dnsDomain" : null
        },
        "user" : {
          "username" : "wwwrun",
          "emailAddress" : null,
          "adUsername" : null,
          "adDomain" : null
        }
      },
      "destination" : {
        "device" : {
          "ipAddress" : "128.164.35.184",
          "port" : 21,
          "macAddress" : "00:17:df:6b:c8:00",
          "dnsHostname" : null,
          "dnsDomain" : null
        },
        "user" : {
          "username" : "wwwrun",
          "emailAddress" : null,
          "adUsername" : null,
          "adDomain" : null
        }
      }
    },
    "domain" : null,
```

```
    "eventSource" : "10.4.61.48:56005",
    "eventSourceId" : "9318"
  } ]
} ],
"pageNumber" : 0,
"pageSize" : 10,
"totalPages" : 1,
"totalItems" : 1,
"hasNext" : false,
"hasPrevious" : false
}
```

Persisting events in an alert

Persist all the events present in the alert using the alert's unique identifier.

```
POST /rest/api/alerts/persist/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the alert.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/alerts/persist/59440ad7e4b0ff674d2cd85e'
-i -X POST \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:54 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 87
```

```
{
  "status" : "SUCCESS",
  "message" : "Persisted alert id 59440ad7e4b0ff674d2cd85e"
}
```

Suspending persist of events in an alert

Suspend all the events present in persist alert using the alert's unique identifier.

```
POST /rest/api/alerts/suspend-persist/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the alert.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/alerts/suspend-
persist/59440ad7e4b0ff674d2cd85e' -i -X POST \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:54 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 99
```

```
{
  "status" : "SUCCESS",
  "message" : "Suspended persist for alert id 59440ad7e4b0ff674d2cd85e"
}
```

Persisting events in an incident

Persist all the events present in the incident using the incident's unique identifier.

```
POST /rest/api/incidents/persist/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/persist/INC-75287' -i -X POST \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Accept: application/json;charset=UTF-8' \
-H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:54 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 106
```

```
{
  "status" : "SUCCESS",
  "message" : "Task successfully submitted to persist incident id - INC-75287"
}
```

Suspending persist of events in an incident

Suspend all the events present in persist incident using the incident's unique identifier.

```
POST /rest/api/incidents/suspend-persist/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/suspend-persist/INC-75287' -i
-X POST \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:54 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 87
```

```
{
  "status" : "SUCCESS",
  "message" : "Suspended persist for incident id INC-75287"
}
```

Get Incident history

Fetch the entire history details of the incident using the incident's unique identifier.

```
POST /rest/api/incidents/history/{id}
```

Path Parameters

Parameter	Description
<code>id</code>	The unique identifier of the incident.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/incidents/history/INC-75287' -i -X POST
\
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:55 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 608
```

```
[ {
  "type" : "STATUS",
  "date" : "2022-05-11T09:24:43.025+00:00",
  "changedBy" : "admin",
  "changedFrom" : "IN_PROGRESS",
  "changedTo" : "REMIEDIATION_REQUESTED"
}, {
  "type" : "PRIORITY",
  "date" : "2022-05-11T09:25:18.767+00:00",
  "changedBy" : "admin",
  "changedFrom" : "HIGH",
  "changedTo" : "MEDIUM"
}, {
  "type" : "ASSIGNEE",
  "date" : "2022-05-11T09:25:31.157+00:00",
  "changedBy" : "admin",
  "changedFrom" : "rolden",
  "changedTo" : "admin"
}, {
  "type" : "CREATED",
  "date" : "2022-05-11T09:20:31.157+00:00",
  "changedBy" : "admin",
  "changedFrom" : null,
  "changedTo" : null
} ]
```

Get Incident Stats

IncidentStats can be retrieved by the date and time they were created. It contains day wise details of the overall MTTA, MTTD and MTTR as well as the count associated with each metric for that day.

```
GET /rest/api/incidents/stats
```

The requested date range can be unbounded, by only supplying either the `since` or `until` parameter, or bounded, by providing both parameters.

Request Parameters

Parameter	Description
pageNumber	The requested page number.
pageSize	The maximum number of items to return in a single page.
since	A date format (e.g., 2022-01-01). Retrieve incidents stats created on and after this date.
until	A date format (e.g., 2022-01-31). Retrieve incident stats created on and before this date.

All results will be returned using the [paginated response payload](#) sorted by the `created` date, in descending order.

Sample Request

```
$ curl
'https://api.netwitness.local/rest/api/incidents/stats?pageSize=100&pageNumber=0&since=2022-05-01&until=2022-05-30' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:15:55 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 290
```

```
{
  "items" : [ {
    "date" : "28-May-22",
    "mtta" : 30,
    "mttaCount" : 3,
    "mttd" : 44,
    "mttdCount" : 1,
    "mttr" : 81,
    "mttrCount" : 1
  } ],
  "pageNumber" : 0,
  "pageSize" : 100,
  "totalPages" : 1,
  "totalItems" : 1,
  "hasNext" : false,
  "hasPrevious" : false
}
```

Get Incident User Stats

Incident User Stats can be retrieved by user and date range. It computes the MTTD values for the range of dates mentioned and responds with a consolidated list.

```
GET /rest/api/incidents/user-stats
```

The requested date range can be unbounded, by only supplying either the `since` or `until` parameter, or bounded, by providing both parameters.

Request Parameters

Snippet request-parameters not found for operation::incident-specification-it/get-incident-user-stats

All results will be returned based on the username input given.

Sample Request

Snippet curl-request not found for operation::incident-specification-it/get-incident-user-stats

Sample Response

Snippet http-response not found for operation::incident-specification-it/get-incident-user-stats

Services Information

Get Service IDs of all Services

The following API lists all services with their service IDs.

The response resource is comprised of the following attributes:

Path	Type	Description
<code>[]</code>	Array	Array of service information.
<code>[][.id]</code>	String	Unique identifier of each service installed in the RSA NetWitness suite.
<code>[][.name]</code>	String	Name of the service. For example, endpoint-server.
<code>[][.displayName]</code>	String	Display name of the service.
<code>[][.host]</code>	String	Host details of the service.
<code>[][.version]</code>	String	Version of the service.

A list of all services can be retrieved using the following API:

```
GET /rest/api/services
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/services' -i -X GET \  
-H 'NetWitness-Token: eyJ...AT' \  
-H 'Accept: application/json; charset=UTF-8' \  
-H 'Content-Type: application/json; charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK  
Content-Type: application/json; charset=UTF-8  
Transfer-Encoding: chunked  
Date: Mon, 12 Dec 2022 09:13:00 GMT  
Keep-Alive: timeout=60  
Connection: keep-alive  
Content-Length: 542
```

```
[ {
  "id" : "5304012d-94c0-42c2-a39f-6720bdab0801",
  "name" : "endpoint-broker-server",
  "displayName" : "Endpoint Broker Server",
  "host" : "endpoint-server",
  "version" : "11.4.0.0"
}, {
  "id" : "5f6e15bb-9384-4666-aa71-e5d134afd7d8",
  "name" : "endpoint-server",
  "displayName" : "Endpoint Server",
  "host" : "endpoint-server",
  "version" : "11.4.0.0"
}, {
  "id" : "f8af0111-f8d4-4fce-b86e-d3efcd073733",
  "name" : "respond-server",
  "displayName" : "Respond Server",
  "host" : "endpoint-server",
  "version" : "11.4.0.0"
} ]
```

Get List of Service IDs by Service Name

```
GET /rest/api/services?name=<service-name>
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/services?name=endpoint-broker-server' -i \
-X GET \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Accept: application/json;charset=UTF-8' \
-H 'Content-Type: application/json;charset=UTF-8'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:00 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 192
```

```
[ {  
  "id" : "5304012d-94c0-42c2-a39f-6720bdab0801",  
  "name" : "endpoint-broker-server",  
  "displayName" : "Endpoint Broker Server",  
  "host" : "endpoint-server",  
  "version" : "11.4.0.0"  
} ]
```

Endpoint APIs

Endpoint Log Hybrid collects and manages endpoint data from hosts. Using the APIs, analyst can:

- View list of host names with agent IDs from one or more Endpoint Servers.
- Retrieve host data, such as drivers, processes, DLLs, files (executables), services, autoruns, security information, anomalies, system configurations, and scripts found on the host.
- Filter hosts on indexed values and sort columns.
- Get list of snapshots and snapshot details for a host.
- Start or stop a scan.
- Get list of files from a specific Endpoint Server.
- Get alerts for a host or file.
- Download file/files to the server.
- Download system and process dump.
- Isolate host from the network.

Note: All endpoint APIs require a service ID to connect to the specific Endpoint Server.

Get Hosts

The Get Hosts API lists all hosts' information from a particular Endpoint Server. It provides a paged response with a standard paged response structure as mentioned in the 'Pagination' section.

The "items" field in paged response consists of individual host information.

Path	Type	Description
items	Array	An array containing the requested resources.
pageNumber	Number	The requested page number.
pageSize	Number	The requested number of items to return in a single page.
totalPages	Number	The total number of pages available.
totalItems	Number	The total number of items available.
hasNext	Boolean	Indicates if there is a page containing results after this page.
hasPrevious	Boolean	Indicates if there is a page containing results before this page.
items[].agentId	String	Agent ID of the host.
items[].hostName	String	Name of the host.
items[].riskScore	Number	Risk score of the host.
items[].networkInterfaces	Array	List of network interfaces with details, such as IP address and MAC address.

Path	Type	Description
items[].networkInterfaces[].name	String	Name of the network interface.
items[].networkInterfaces[].macAddress	String	MAC Address of the network interface.
items[].networkInterfaces[].ipv4	Array	List of IPV4 in the network interface.
items[].networkInterfaces[].ipv6	Array	List of IPV6 in the network interface.
items[].networkInterfaces[].networkIdv6	Array	List of network IDV6 in the network interface.
items[].networkInterfaces[].gateway	Array	List of gateway in the network interface.
items[].networkInterfaces[].dns	Array	List of DNS in the network interface.
items[].networkInterfaces[].promiscuous	String	Specifies if the network interface is in the promiscuous mode.
items[].lastSeenTime	String	Agent last seen time.

```
GET /rest/api/hosts?serviceId=<service-id>&pageNumber=0&pageSize=100
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/hosts?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&pageNumber=0&pageSize=1' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:01 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 691
```

```

{
  "items" : [ {
    "agentId" : "B27DDED7-6FFA-A9D3-6577-3DDE367B2820",
    "hostName" : "WIN-854PACLCQ07-VC",
    "riskScore" : 0,
    "networkInterfaces" : [ {
      "name" : "Intel(R) 82574L Gigabit Network Connection",
      "macAddress" : "00:50:56:01:1B:31",
      "ipv4" : [ "10.40.15.202" ],
      "ipv6" : [ "fe80::651d:c035:a19b:ea03%13" ],
      "networkIdv6" : [ "fe80::%13" ],
      "gateway" : [ "10.40.12.1" ],
      "dns" : [ "10.31.64.22", "10.31.64.23" ],
      "promiscuous" : false
    } ],
    "lastSeenTime" : "2019-01-28T09:25:02.484Z"
  } ],
  "pageNumber" : 0,
  "pageSize" : 1,
  "totalPages" : 2,
  "totalItems" : 2,
  "hasNext" : true,
  "hasPrevious" : false
}

```

Get Hosts with Filter

The following fields are supported for filtering and sorting on Get Hosts API - 'agentId', 'hostName', 'riskScore' and 'networkInterfaces.ipv4'.

Filter and sort are specified as a part of the request body.

Sample Request

```

$ curl 'https://api.netwitness.local/rest/api/hosts?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&pageNumber=0&pageSize=1' -i -X GET \
  -H 'Accept: application/json; charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Content-Type: application/json' \
  -d
'{"criteria":{"criteriaList":[{"criteriaList":[],"expressionList":[{"propertyName":"hostName","restrictionType":"LIKE","propertyValues":[{"value":"WIN-854PACLCQ07-VC","relative":false}]}],"predicateType":"AND"}, {"criteriaList":[],"expressionList":[{"propertyName":"riskScore","restrictionType":"BETWEEN","propertyValues":[{"value":0,"relative":false}, {"value":100,"relative":false}]}],"predicateType":"OR"}], "expressionList": [{"criteriaList":[],"predicateType":"AND", "sort":{"keys":["riskScore"],"descending":true}}}'

```


HTTP request

```
GET /rest/api/hosts?serviceId=5f6e15bb-9384-4666-aa71-
e5d134afd7d8&pageNumber=0&pageSize=1 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 498
```

```
{"criteria":{"criteriaList":[{"criteriaList":[],"expressionList":[{"propertyName":"hostName","restrictionType":"LIKE","propertyValues":[{"value":"WIN-854PACLQ07-VC","relative":false}]}],"predicateType":"AND"},{"criteriaList":[],"expressionList":[{"propertyName":"riskScore","restrictionType":"BETWEEN","propertyValues":[{"value":0,"relative":false},{"value":100,"relative":false}]}],"predicateType":"OR"}],"expressionList":[{"predicateType":"AND"},"sort":{"keys":["riskScore"],"descending":true}}
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:03 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 692
```

```

{
  "items" : [ {
    "agentId" : "B27DDED7-6FFA-A9D3-6577-3DDE367B2820",
    "hostName" : "WIN-854PAQLCQ07-VC",
    "riskScore" : 0,
    "networkInterfaces" : [ {
      "name" : "Intel(R) 82574L Gigabit Network Connection",
      "macAddress" : "00:50:56:01:1B:31",
      "ipv4" : [ "10.40.15.202" ],
      "ipv6" : [ "fe80::651d:c035:a19b:ea03%13" ],
      "networkIdv6" : [ "fe80::%13" ],
      "gateway" : [ "10.40.12.1" ],
      "dns" : [ "10.31.64.22", "10.31.64.23" ],
      "promiscuous" : false
    } ],
    "lastSeenTime" : "2019-01-28T09:25:02.484Z"
  } ],
  "pageNumber" : 0,
  "pageSize" : 1,
  "totalPages" : 1,
  "totalItems" : 1,
  "hasNext" : false,
  "hasPrevious" : false
}

```

The following is an example for filter criteria in the request body:

```

{
  "criteria": {
    "criteriaList": [
      {
        "expressionList": [{ "propertyName": "agentId", "restrictionType":
"EQUAL", "propertyValues": [{"value": "2F53FC2C-A737-B34B-6813-12E48379C15D"}]}]
      }
    ]
  }
}

```

The following are the supported 'restrictionType'

- Operators that require no value: IS_NULL, IS_NOT_NULL.
- Operators that require one value: LIKE, NOT_LIKE, EQUAL, NOT_EQUAL, LESS_THAN, LESS_THAN_OR_EQUAL_TO, GREATER_THAN, GREATER_THAN_OR_EQUAL_TO.
- Operators that require two value: BETWEEN, NOT_BETWEEN.
- Operators that uses multiple value: IN, NOT_IN.

The following are the supported 'predicateType' - AND, OR, NOT.

Get List of Snapshots for Host

This API provides a list of snapshots, which are IDs to fetch the snapshot details of the host.

```
GET /rest/api/host/<Host-Agent-Id>/snapshots?serviceId=<service-id>
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/snapshots?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:03 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 30
```

```
[ "2017-12-22T14:34:05.985Z" ]
```

Get Snapshot Details for the Host

This API provides snapshot details of the given host for the provided snapshot time.

Response Fields

Path	Type	Description
[]	Array	Array of scan snapshot for the agent.
[][.machineOsType]	String	Type of operating system (Windows, Mac, Linux).
[][.hostName]	String	Name of the host.
[][.agentId]	String	Agent ID of the host.
[][.agentVersion]	String	Version of the agent.
[][.scanStartTime]	String	Start time of the scan snapshot.
[][.directory]	String	Directory of the file.
[][.fileName]	String	Name of the file.

Path	Type	Description
[].owner.username	String	User name of the owner of the file.
[].owner.groupname	String	Group name of the owner of the file.
[].owner.uid	String	UID of the user name.
[].owner.gid	String	GID of the user name.
[].timeCreated	String	Time when file was created.
[].timeModified	String	Time when file was modified.
[].timeAccessed	String	Time when file was last accessed.
[].attributes	Array	List of file attributes.
[].accessMode	Number	Access mode of the file.
[].sameDirectoryFileCounts.nonExe	Number	Number of non-exe files in the same directory of the file.
[].sameDirectoryFileCounts.exe	Number	Number of exe files in the same directory of the file.
[].sameDirectoryFileCounts.subFolder	Number	Number of sub-folders in the same directory of the file.
[].sameDirectoryFileCounts.exeSameCompany	Number	Number of executables with the same company name in the same directory of the file.
[].sameDirectoryFileCounts.hiddenFiles	Number	Count of hidden files in the same directory of the file.
[].fileContext	Array	List of file context.
[].directoryContext	Array	List of directory context.
[].autorunContext	Array	List of autorun context.
[].networkContext	Array	List of network context.
[].kernelModeContext	Array	List of kernel mode context.
[].userModeContext	Array	List of user mode context.
[].processContext	Array	List of process context.
[].rpm.packageName	String	RPM package name to which the file belongs.
[].rpm.category	String	Category to which the rpm package belongs.
[].windows.processes[].eProcess	String	Identifier of the process.
[].windows.processes[].sessionId	Number	Session ID of the process.
[].windows.processes[].parentPath	String	Directory of the parent process.
[].windows.processes[].imageSize	Number	Size of the process image.
[].windows.processes[].integrityLevel	Number	Integrity level of the process.
[].windows.processes[].context	Array	List of process context.
[].windows.processes[].pid	Number	ID of the process.
[].windows.processes[].parentPid	Number	ID of the parent process.

Path	Type	Description
[].windows.processes[].imageBase	Number	Base address of the process.
[].windows.processes[].createUtcTime	String	Creation time of the process.
[].windows.processes[].owner	String	Name of the user.
[].windows.processes[].launchArguments	String	Launch arguments of the process.
[].windows.processes[].threadCount	Number	Number of threads running in the process.
[].windows.dlls[].createTime	String	Creation time of the process.
[].windows.dlls[].eprocess	String	Identity of the process.
[].windows.dlls[].imageSize	Number	Size of the DLL image in memory.
[].windows.threads[].processName	String	Name of the process.
[].windows.threads[].processTime	String	Creation time of the process.
[].windows.threads[].eprocess	String	Identifier of the process.
[].windows.threads[].pid	Number	PID of the process.
[].windows.threads[].ethread	String	Identifier of the thread.
[].windows.threads[].tid	Number	ID of the thread.
[].windows.threads[].teb	String	Address of thread environment block.
[].windows.threads[].startAddress	String	Start address of the thread in memory.
[].windows.threads[].state	Array	Thread state.
[].windows.threads[].behaviorKey	String	Floating behavior resolution of the thread.
[].windows.drivers[].windows.imageBase	Number	Base address of the driver image.
[].windows.drivers[].windows.imageSize	Number	Size of the driver image.
[].windows.services[].windows.serviceName	String	Service name as identified by the system.
[].windows.services[].displayName	String	Display name for the service.
[].windows.services[].description	String	Description of the service.
[].windows.services[].account	String	Name of the user the service executes as.
[].windows.services[].launchArguments	String	Launch arguments of the service.
[].windows.services[].windows.serviceMain	String	Service's main.
[].windows.services[].hostingPid	Number	Service's hosting process ID.

Path	Type	Description
[].windows.services[].state	String	Current state of the service.
[].windows.services[].win32Error Code	Number	Last Windows 32 error code from registry.
[].windows.services[].context	Array	List of service context.
[].windows.tasks[].name	String	Name of the task.
[].windows.tasks[].executeUser	String	Name of the user the task executes as.
[].windows.tasks[].creatorUser	String	Name of the user who created the task.
[].windows.tasks[].launchArguments	String	Launch arguments of the task.
[].windows.tasks[].status	Array	Status of the task.
[].windows.tasks[].lastRunTime	String	Time when the task was last run.
[].windows.tasks[].nextRunTime	String	Next scheduled time of the task.
[].windows.tasks[].triggerString	String	Textual trigger string of the task.
[].windows.autoruns[].type	String	Type of the autorun.
[].windows.autoruns[].registryPath	String	Registry path where autorun is located.
[].windows.autoruns[].launchArguments	String	Launch argument of the autorun.
[].windows.imageHooks[].process.pid	String	PID of the process in which hook was detected.
[].windows.imageHooks[].process.fileName	String	Filename of the process in which hook was detected.
[].windows.imageHooks[].process.createUtcTime	String	Creation time of the process in which hook was detected.
[].windows.imageHooks[].hookLocation.section	String	Name of the image section that was modified by the hook.
[].windows.imageHooks[].hookLocation.sectionBase	String	Base of the image section that was modified by the hook.
[].windows.imageHooks[].hookLocation.symbol	String	Closest symbol name to the memory location that was modified.
[].windows.imageHooks[].hookLocation.symbolOffset	Number	Closest symbol +/- offset to the hook location when relevant.
[].windows.imageHooks[].inlinePatch.originalBytes	String	Hexadecimal bytes which were replaced.
[].windows.imageHooks[].inlinePatch.originalAsm	Array	Array of decoded ASM instructions that were replaced.
[].windows.imageHooks[].inlinePatch.currentBytes	String	Hexadecimal bytes which have overwritten the original code.
[].windows.imageHooks[].inlinePatch.currentAsm	Array	Array of decoded ASM instructions that have overwritten the original code.

Path	Type	Description
[].windows.kernelHooks[].hookLocation.objectName	String	Name of the object that was hooked in kernel.
[].windows.kernelHooks[].hookLocation.objectFunction	String	Name of the object function that was hooked in kernel.
[].mac.processes[].priority	Number	Priority of the process.
[].mac.processes[].flags	Number	Process flags.
[].mac.processes[].nice	Number	Nice value of process.
[].mac.processes[].openFilesCount	Number	Number of open files by process at scan time.
[].mac.processes[].context	Array	Process context.
[].mac.processes[].pid	Number	ID of the process.
[].mac.processes[].parentPid	Number	ID of the parent process.
[].mac.processes[].imageBase	Number	Base address of the process.
[].mac.processes[].createUtcTime	String	Creation time of the process.
[].mac.processes[].owner	String	Name of the user.
[].mac.processes[].launchArguments	String	Launch arguments of the process.
[].mac.processes[].threadCount	Number	Number of threads running in the process.
[].mac.dylibs[].pid	Number	Process ID in dylib which is loaded.
[].mac.dylibs[].processName	String	Name of the process.
[].mac.dylibs[].imageBase	String	Base address of image in the process.
[].mac.drivers[].preLinked	Boolean	True if Kext bundle is prelinked.
[].mac.drivers[].numberOfReferences	Number	Number of references.
[].mac.drivers[].dependencies	Array	List of kexts(name) the driver is linked against.
[].mac.drivers[].imageBase	String	Base address of the driver image.
[].mac.drivers[].imageSize	String	Size of the driver image.
[].mac.daemons[].name	String	Label of the daemon.
[].mac.daemons[].sessionName	String	Name of the session in which daemon runs.
[].mac.daemons[].user	String	Name of the user under which the daemon runs.
[].mac.daemons[].pid	Number	ID of the process.
[].mac.daemons[].onDemand	Boolean	True if daemon is configured to run on demand.
[].mac.daemons[].lastExitCode	Number	Last exit code.
[].mac.daemons[].timeout	Number	Time out value.
[].mac.daemons[].daemons.launchArguments	String	Launch argument of the daemon.
[].mac.daemons[].daemons.configFile	String	Full path of the configuration file used to configure this daemon.

Path	Type	Description
[].mac.tasks[].name	String	Name of the task.
[].mac.tasks[].cronJob	Boolean	True if the task is cron job, else launchd.
[].mac.tasks[].launchArguments	String	Launch argument of the task.
[].mac.tasks[].user	String	Name of the user under which this task will run.
[].mac.tasks[].triggerString	String	Trigger string of the task.
[].mac.tasks[].configFile	String	Full path of the configuration file used to configure this task.
[].mac.autoruns[].type	String	Type of autorun.
[].mac.autoruns[].user	String	Name of the user under which the autorun is run.
[].mac.autoruns[].name	String	Label of the autorun.
[].mac.autoruns[].detail	String	Details of the autorun.
[].linux.processes[].priority	Number	Priority of the process.
[].linux.processes[].uid	Number	UID of the user.
[].linux.processes[].environment	String	Environment variables.
[].linux.processes[].nice	Number	Nice value of the process.
[].linux.processes[].securityContext	String	Security context.
[].linux.processes[].pid	Number	ID of the process.
[].linux.processes[].parentPid	Number	ID of the parent process.
[].linux.processes[].imageBase	Number	Base address of the process.
[].linux.processes[].createUtcTime	String	Time of creation of the process.
[].linux.processes[].owner	String	Name of the user.
[].linux.processes[].launchArguments	String	Launch arguments of the process.
[].linux.processes[].threadCount	Number	Number of threads running in the process.
[].linux.loadedLibraries[].pid	String	Process ID in which library is loaded.
[].linux.loadedLibraries[].processName	String	Name of the process.
[].linux.loadedLibraries[].imageBase	String	Base address of image in the process.
[].linux.drivers[].numberOfInstances	Number	Number of instances loaded in memory.
[].linux.drivers[].loadState	String	Load state of the driver.
[].linux.drivers[].dependencies	Array	Dependent driver names.
[].linux.drivers[].author	String	Name of the author of driver.
[].linux.drivers[].description	String	Description of the driver.

Path	Type	Description
[].linux.drivers[].sourceVersion	String	Source version of the driver.
[].linux.drivers[].versionMagic	String	Version magic of the driver.
[].linux.initds[].initdHashSha256	String	Hash of the init-d script file.
[].linux.initds[].initdPaths	String	Path of the init-d script file.
[].linux.initds[].pid	Number	ID of the process.
[].linux.initds[].description	String	Description of the init-d.
[].linux.initds[].status	String	Status of the init-d.
[].linux.initds[].runLevels	Array	List of run levels in which the init-d is enabled.
[].linux.systemds[].systemdHashSha256	String	Hash value of the systemd script file.
[].linux.systemds[].systemdPaths	String	Path value of the systemd script file.
[].linux.systemds[].name	String	Name of the systemd.
[].linux.systemds[].description	String	Description of the systemd.
[].linux.systemds[].state	String	State of the systemd.
[].linux.systemds[].launchArguments	String	Launch argument of the systemd.
[].linux.systemds[].pid	Number	ID of the process.
[].linux.systemds[].triggeredBy	Array	Triggered by list of the systemd.
[].linux.systemds[].triggerStrings	Array	Trigger strings of the systemd.
[].linux.autoruns[].type	String	Type of autorun.
[].linux.autoruns[].label	String	Label of the autorun.
[].linux.autoruns[].comments	String	Comments of the autorun.
[].linux.crons[].user	String	User account under which cron job was created.
[].linux.crons[].triggerString	String	Trigger string that would launch the cron job.
[].linux.crons[].launchArguments	String	Launch arguments of the cron job.
firstFileName	String	First name of the file sent by the agent.
reputationStatus	String	Reputation status of the file.
globalRiskScore	String	Global risk score.
firstSeenTime	String	Time when the file was first seen by the Endpoint Server.
machineOsType	String	Type of operating system (Windows, Mac, Linux).
signature	Object	Signatory information of the file.
signature.timeStamp	String	Timestamp of the signature.
signature.thumbprint	String	Thumbprint of the certificate.
signature.context	Array	Context information of the certificate.
signature.signer	String	Signer information of the certificate.

Path	Type	Description
size	String	Size of the file.
checksumMd5	String	MD5 of the file.
checksumSha1	String	SHA1 of the file.
checksumSha256	String	SHA256 of the file.
pe	Object	PE information of the file. This is applicable for Windows files.
pe.timeStamp	String	Timestamp of the PE File.
pe.imageSize	String	Image size of the PE file.
pe.numberOfExportedFunctions	String	Number of exported function in the PE file.
pe.numberOfNamesExported	String	Number of names exported in the PE file.
pe.numberOfExecuteWriteSections	String	Number of execute write sections in the PE file.
pe.context	Array	Context information of the PE file.
pe.resources	Object	Resources of the PE file.
pe.resources.originalFileName	String	Original filename as per PE information.
pe.resources.company	String	Company name as per PE information.
pe.resources.description	String	Description of the file as per PE information.
pe.resources.version	String	Version of the file as per PE information.
pe.sectionNames	Array	List of section names in the PE file.
pe.importedLibraries	Array	List of imported libraries in the PE file.
elf	Object	ELF information of the file. This is applicable for Linux files.
elf.classType	String	Class type of the ELF file.
elf.data	String	Data of ELF file.
elf.entryPoint	String	Entry point for the ELF file.
elf.context	Array	Context information of ELF file.
elf.type	String	Type of ELF file.
elf.sectionNames	Array	List of section names in ELF file.
elf.importedLibraries	Array	List of imported libraries in ELF file.
macho	Object	Macho information of the file. This is applicable for Mac files.
macho.uuid	String	UUID of the Macho file.
macho.identifier	String	Identifier of the Macho file.
macho.minOsxVersion	String	Minimum OSX version for the Macho file.
macho.context	Array	Context information of the Macho file.
macho.flags	String	Flags of Macho file.
macho.numberOfLoadCommands	String	Number of load commands for the Macho file.
macho.version	String	Version of the Macho file.

Path	Type	Description
<code>macho.sectionNames</code>	Array	Section names in the Macho file.
<code>macho.importedLibraries</code>	Array	Imported libraries list in the Macho file.
<code>entropy</code>	String	Entropy of the file.
<code>format</code>	String	Format of the file.
<code>fileStatus</code>	String	Status of the file as assigned by the analyst. (Whitelist, Blacklist, Neutral, and Graylist).
<code>remediationAction</code>	String	Remediation action as assigned by the analyst. For example, Blocked.
<code>[].localRiskScore</code>	Number	File's score based on alerts triggered in the given agent.

```
GET /rest/api/host/<Host-Agent-Id>/snapshots/2019-06-17T04:24:14.608Z?serviceId=<service-id>
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/snapshots/2017-12-22T14%3A34%3A05.985Z?serviceId=67a84b72-3d9a-4377-9096-7e6af9f13306' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 22 Jul 2019 08:34:38 GMT
Content-Length: 6710
Content-Disposition: inline;filename=f.txt
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
```

```
[ {
  "machineOsType" : "windows",
  "hostName" : "HOSTNAME",
  "agentId" : "B27DDED7-6FFA-A9D3-6577-3DDE367B2820",
  "agentVersion" : "11.1.0.0",
  "scanStartTime" : "2017-12-22T14:34:05.985Z",
  "directory" : "F\\SonarQube\\DIRECTCP\\PolicyDefinitions",
  "fileName" : "shtctky.bat",
  "owner" : {
    "username" : "Sinha, Vidya",
    "groupname" : "CORP",
```

```

    "uid" : 9,
    "gid" : 1
  },
  "timeCreated" : "2017-12-22T10:00:15.000Z",
  "timeModified" : "2017-12-22T06:00:15.000Z",
  "timeAccessed" : "2017-12-22T11:00:15.000Z",
  "attributes" : null,
  "accessMode" : 15,
  "sameDirectoryFileCounts" : {
    "nonExe" : 1,
    "exe" : 4,
    "subFolder" : 0,
    "exeSameCompany" : 3,
    "hiddenFiles" : 0
  },
  "fileContext" : [ "ads", "accessDenied", "hiddenDifferentialView", "encrypted" ],
  "directoryContext" : [ "desktop" ],
  "autorunContext" : [ "winlogon" ],
  "networkContext" : [ "accessNetwork", "listen" ],
  "kernelModeContext" : [ "loaded", "hookEat", "hookSsdT", "createThreadNotification",
"imageMismatch", "remoteThreadCreator" ],
  "userModeContext" : [ "loaded", "hookEat", "mapped", "image", "threadFloating",
"remoteMemoryAllocator", "setWindowsHook" ],
  "processContext" : [ "accessDenied", "dyldInserted", "ldPreloaded" ],
  "rpm" : null,
  "windows" : {
    "processes" : [ {
      "pid" : 46270,
      "parentPid" : 4,
      "imageBase" : 55076,
      "createUtcTime" : null,
      "owner" : "Sinha, Vidya",
      "launchArguments" : "/B /nologo %systemroot%\system32\calluxxprovider.vbs
$(Arg0) $(Arg1) $(Arg2)",
      "threadCount" : 0,
      "eProcess" : "0x8F76",
      "sessionId" : 1,
      "parentPath" : null,
      "imageSize" : 0,
      "integrityLevel" : 0,
      "context" : [ "UsingNamedPipe" ]
    } ],
    "dlls" : [ {
      "pid" : 46270,
      "processName" : null,
      "imageBase" : 55590,
      "createTime" : "2017-12-22T16:00:15.000+0000",
      "eProcess" : "0x3DFE",
      "imageSize" : 55459
    } ],
    "threads" : [ ],

```

```

"drivers" : [ ],
"services" : [ {
  "serviceName" : "wlanext",
  "displayName" : "wlanext",
  "description" : "wlanext description",
  "account" : "Sinha, Vidya",
  "launchArguments" : "-id 1",
  "serviceMain" : "ServiceMain",
  "hostingPid" : 0,
  "state" : null,
  "win32ErrorCode" : 26218,
  "context" : null
} ],
"tasks" : [ {
  "name" : "Shaktiman",
  "executeUser" : "Sinha, Vidya",
  "creatorUser" : "Sinha, Vidya",
  "launchArguments" : "-Embedding",
  "status" : null,
  "lastRunTime" : null,
  "nextRunTime" : null,
  "triggerString" : null
} ],
"autoruns" : [ ],
"imageHooks" : [ ],
"kernelHooks" : [ ]
},
"mac" : null,
"linux" : null,
"fileProperties" : null,
"localRiskScore" : 0
} ]

```

To filter the snapshot details based on the category, the following fields can be provided as path parameter - PROCESSES, LOADED_LIBRARIES, SERVICES, AUTORUNS, TASKS, DRIVERS, THREADS, IMAGE_HOOKS, and KERNEL_HOOKS.

```

GET /rest/api/host/<Host-Agent-Id>/snapshots/2019-06-17T04:24:14.608Z?serviceId=<service-id>&categories=PROCESSES

```

Get Files

This API lists all related information of files from a specific Endpoint Server. These information are specific to the unique file and does not include any host information.

It provides a paged response with a standard paged response structure as mentioned in the 'Pagination' section.

The "items" field in paged response consists of individual file information.

Path	Type	Description
items[].pe.resources.company	String	Company name as per PE information.
items[].pe.resources.description	String	Description of the file as per PE information.
items[].pe.resources.version	String	Version of the file as per PE information.
items[].pe.sectionNames	Array	List of section names in the PE file.
items[].pe.importedLibraries	Array	List of imported libraries in the PE file.
items[].elf	Object	ELF information of the file. This is applicable for Linux files.
items[].elf.classType	String	Class type of the ELF file.
items[].elf.data	String	Data of ELF file.
items[].elf.entryPoint	String	Entry point for the ELF file.
items[].elf.context	Array	Context information of ELF file.
items[].elf.type	String	Type of ELF file.
items[].elf.sectionNames	Array	List of section names in ELF file.
items[].elf.importedLibraries	Array	List of imported libraries in ELF file.
items[].macho	Object	Macho information of the file. This is applicable for Mac files.
items[].macho.uuid	String	UUID of the Macho file.
items[].macho.identifier	String	Identifier of the Macho file.
items[].macho.minOsxVersion	String	Minimum OSX version for the Macho file.
items[].macho.context	Array	Context information of the Macho file.
items[].macho.flags	String	Flags of Macho file.
items[].macho.numberOfLoadCommands	String	Number of load commands for the Macho file.
items[].macho.version	String	Version of the Macho file.
items[].macho.sectionNames	Array	Section names in the Macho file.
items[].macho.importedLibraries	Array	Imported libraries list in the Macho file.
items[].entropy	String	Entropy of the file.
items[].format	String	Format of the file.
items[].fileStatus	String	Status of the file as assigned by the analyst. (Whitelist, Blacklist, Neutral, and Graylist).
items[].remediationAction	String	Remediation action as assigned by the analyst. For example, Blocked.

Note: The following is a sample response with all fields populated. However, the response for pe, macho, and elf is generated based the operating system type. The fields without values will display as null.

```
GET /rest/api/files?serviceId=<service-id>&pageNumber=0&pageSize=90
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/files?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&pageNumber=0&pageSize=1' -i -X GET \  
-H 'Accept: application/json;charset=UTF-8' \  
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Transfer-Encoding: chunked  
Date: Mon, 12 Dec 2022 09:13:05 GMT  
Keep-Alive: timeout=60  
Connection: keep-alive  
Content-Length: 2054
```

```
{  
  "items" : [ {  
    "firstFileName" : "cmd.exe",  
    "reputationStatus" : "Known",  
    "globalRiskScore" : 0,  
    "firstSeenTime" : "2019-04-28T05:40:20.000Z",  
    "machineOsType" : "windows",  
    "signature" : {  
      "timeStamp" : "2019-04-28T05:40:20.000Z",  
      "thumbprint" : "ae9c1ae54763822eec42474983d8b635116c8452",  
      "context" : [ "microsoft", "signed", "valid", "catalog" ],  
      "signer" : "Microsoft Windows"  
    },  
    "size" : 278528,  
    "checksumMd5" : "0d088f5bcfa8f086fba163647cd80cab",  
    "checksumSha1" : "08cc2e8dca652bdda1acca9c446560d4bc1bcdf9",  
    "checksumSha256" :  
    "9023f8aaeda4a1da45ac477a81b5bbe4128e413f19a0abfa3715465ad66ed5cd",  
    "pe" : {  
      "timeStamp" : "2019-04-28T05:40:20.000Z",  
      "imageSize" : 413696,  
      "numberOfExportedFunctions" : 0,  
      "numberOfNamesExported" : 0,  
      "numberOfExecuteWriteSections" : 0,  
      "context" : [ "file.exe" ],  
      "resources" : {  
        "originalFileName" : "Cmd.Exe",  
        "company" : "Microsoft Corporation",  
        "description" : "Windows Command Processor",  
        "version" : null  
      }  
    }  
  } ]  
}
```



```

    },
    "sectionNames" : [ ".text" ],
    "importedLibraries" : [ "msvcrt.dll" ]
  },
  "elf" : {
    "classType" : 0,
    "data" : 0,
    "entryPoint" : 0,
    "context" : [ "file.arch64", "file.lkm" ],
    "type" : 1,
    "sectionNames" : [ ".note.gnu.build-id", ".text" ],
    "importedLibraries" : null
  },
  "macho" : {
    "uuid" : "277163DE-842E-390D-A7FF-EC4CF2D211A4",
    "identifier" : "com.apple.geod",
    "minOsxVersion" : "10.11.0",
    "context" : [ "file.arch64" ],
    "flags" : 2097285,
    "numberOfLoadCommands" : 22,
    "version" : "1151.49.1",
    "sectionNames" : [ "__PAGEZERO" ],
    "importedLibraries" : [ "Foundation" ]
  },
  "entropy" : 6.17224886172381,
  "format" : "pe",
  "fileStatus" : "Blacklist",
  "remediationAction" : "Unblock"
} ],
"pageNumber" : 0,
"pageSize" : 1,
"totalPages" : 2,
"totalItems" : 2,
"hasNext" : true,
"hasPrevious" : false
}

```

Request Scan

This API starts a scan for the host with the specified agent ID.

```
POST /rest/api/host/{agentId}/scan?serviceId=<service-id>&scanType=<scanType>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.
<code>scanType</code>	Type of scan command.
<code>cpuMax</code>	You can use <code>cpuMax</code> to specify the amount of CPU the agent can use to run the scan. You can choose a value from 5 to 100. If you do not specify a value, the agent uses the default 25% CPU for the scan

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/scan?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&scanType=QUICK_SCAN&cpuMax=67' -i -X POST \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/x-www-form-urlencoded; charset=ISO-8859-1'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:05 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Request Scan with given CPU Usage

This API starts a scan for the host with the specified agent ID and given CPU usage.

```
POST /rest/api/host/{agentId}/scan?serviceId=<service-id>&scanType=<scanType>&cpuMax=<cpuMax>
```

Path Parameters

Snippet path-parameters not found for operation::endpoint-api-specification-it/request-scan-for-a-host-with-cpuMax/

Request Parameters

Snippet request-parameters not found for operation::endpoint-api-specification-it/request-scan-for-a-host-with-cpuMax/

Sample Request

Snippet curl-request not found for operation::endpoint-api-specification-it/request-scan-for-a-host-with-cpuMax/

Sample Response

Snippet http-response not found for operation::endpoint-api-specification-it/request-scan-for-a-host-with-cpuMax/

- cpuMax: Minimum value allowed is 5 and Maximum value allowed is 100.

Request Stop Scan

This API stops a scan for the host with the specified agent ID.

```
DELETE /rest/api/host/{agentId}/scan?serviceId=<service-id>&scanType=<scanType>
```

Path Parameters

Parameter	Description
agentId	Unique identifier of the host.

Request Parameters

Parameter	Description
serviceId	Service ID of the Endpoint Server to be connected.
scanType	Type of scan command.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/scan?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&scanType=CANCEL_SCAN' -i -X DELETE \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:05 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Get Alerts for a Host

This API gets all alerts triggered for a given host. Alerts are categorized as 'Critical', 'High', 'Medium' and 'Low'. The response provides category level count of alerts triggered along with list of alerts.

Path	Type	Description
<code>id</code>	String	ID of the entity for which score needs to be queried. Agent ID in case of host and checksum in case of files.
<code>distinctAlertCount</code>	Object	Count of distinct Alert/category for the entity.
<code>distinctAlertCount.critical</code>	String	Number of critical alerts.
<code>distinctAlertCount.high</code>	String	Number of high alerts.
<code>distinctAlertCount.medium</code>	String	Number of medium alerts.
<code>distinctAlertCount.low</code>	String	Number of low alerts.
<code>categorizedAlerts</code>	String	Count of alert and events for a file/host, categorized by severity.

```
GET /rest/api/host/{agentId}/alerts?serviceId=<service-id>
```

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/alerts?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X GET \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:05 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 855
```

```

{
  "id" : "B27DDED7-6FFA-A9D3-6577-3DDE367B2820",
  "distinctAlertCount" : {
    "critical" : 0,
    "high" : 4,
    "medium" : 2,
    "low" : 0
  },
  "categorizedAlerts" : {
    "High" : {
      "Possibly Renamed net.exe Detected" : {
        "alertCount" : 1,
        "eventCount" : 1
      },
      "Powershell Injects Remote Process" : {
        "alertCount" : 3,
        "eventCount" : 3
      },
      "Unexpected taskhostw.exe Parent" : {
        "alertCount" : 1,
        "eventCount" : 1
      },
      "Unexpected runtimebroker.exe Parent" : {
        "alertCount" : 1,
        "eventCount" : 1
      }
    },
    "Medium" : {
      "Performs Scripted File Transfer" : {
        "alertCount" : 1,
        "eventCount" : 1
      },
      "Unexpected Svchost.Exe Parent" : {
        "alertCount" : 1,
        "eventCount" : 1
      }
    }
  }
}

```

To filter alerts based on the category, add the alertCategory path parameter.

```
GET /rest/api/host/{agentId}/alerts?serviceId=<service-id>&alertCategory=Medium
```

Get Alerts for a File

This API gets all alerts triggered for a given file. Alerts are categorized as 'Critical', 'High', 'Medium' and 'Low'. The response provides category level count of alerts triggered along with list of alerts.

Only checksum supported are `sha256` and `md5`.

Path	Type	Description
<code>id</code>	<code>String</code>	ID of the entity for which score needs to be queried. Agent ID in case of host and checksum in case of files.
<code>distinctAlertCount</code>	<code>Object</code>	Count of distinct Alert/category for the entity.
<code>distinctAlertCount.critical</code>	<code>String</code>	Number of critical alerts.
<code>distinctAlertCount.high</code>	<code>String</code>	Number of high alerts.
<code>distinctAlertCount.medium</code>	<code>String</code>	Number of medium alerts.
<code>distinctAlertCount.low</code>	<code>String</code>	Number of low alerts.
<code>categorizedAlerts</code>	<code>String</code>	Count of alert and events for a file/host, categorized by severity.

```
GET /rest/api/file/{checksum}/alerts?serviceId=<service-id>
```

Sample Request

```
$ curl
'https://api.netwitness.local/rest/api/file/d1c79a36593f0d5f7d07502b963d97acc851dc0291
f4556ce8f110a58a48fda4/alerts?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X
GET \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT'
```

Sample Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
Content-Length: 569
```

```

{
  "id" : "d1c79a36593f0d5f7d07502b963d97acc851dc0291f4556ce8f110a58a48fda4",
  "distinctAlertCount" : {
    "critical" : 0,
    "high" : 2,
    "medium" : 1,
    "low" : 0
  },
  "categorizedAlerts" : {
    "High" : {
      "Possibly Renamed net.exe Detected" : {
        "alertCount" : 1,
        "eventCount" : 1
      },
      "Powershell Injects Remote Process" : {
        "alertCount" : 3,
        "eventCount" : 3
      }
    },
    "Medium" : {
      "Performs Scripted File Transfer" : {
        "alertCount" : 1,
        "eventCount" : 1
      }
    }
  }
}

```

To filter alerts based on the category, add the alertCategory path parameter.

```
GET /rest/api/file/{checksum}/alerts?serviceId=<service-id>&alertCategory=Medium
```

Request File Download to Server

This API initiates the file download to the Endpoint Server. The following are the fields in the request body:

- path: Full path where the files may be present.

```
POST /rest/api/host/{agentId}/download/download-file?serviceId=<service-id>
```

Path Parameters

Parameter	Description
agentId	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/download-file?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X POST \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/json' \
-d '{"path": "C:\\Users\\sample\\test.exe"}'
```

HTTP request

```
POST /rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/download-file?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 38

{"path": "C:\\Users\\sample\\test.exe"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Request Multiple File Downloads to Server

This API initiates the multiple file downloads to the Endpoint Server matching the wildcard path. The following are the fields in the request body:

- `path`: Path where the files may be present using wildcard.
- `countFiles`: Maximum number of files returned by the host matching the wildcard path (default 10).

- `maxFileSize`: Maximum size of each file (in MB) (default 100 MB).

```
POST /rest/api/host/{agentId}/download/download-files?serviceId=<service-id>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/download-files?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8'
-i -X POST \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Content-Type: application/json' \
  -d '{"path":"C:\\Users\\sample\\*", "countFiles":3, "maxFileSize":150}'
```

HTTP request

```
POST /rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/download-files?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 64

{"path":"C:\\Users\\sample\\*", "countFiles":3, "maxFileSize":150}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Request MFT Download

This API initiates the MFT download to the Endpoint Server.

```
POST /rest/api/host/{agentId}/download/mft?serviceId=<service-id>&path=<path>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.
<code>path</code>	Drive or NTFS Mount path for which MFT is requested

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/mft?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8&path=E%3A%5C' -i -X POST \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Content-Type: application/x-www-form-urlencoded; charset=ISO-8859-1'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Request parameter "path" can be any valid windows drive or windows path. Below are the valid sample values

- C:\
- d:\

- E:\mountPath\NTFSmount
- f:\mount path\NTFS Mount

Note: MFT Download is not supported in Relay Mode

Request System Dump Download

This API initiates the download of the system dump to the Endpoint Server.

```
POST /rest/api/host/{agentId}/download/system-dump?serviceId=<service-id>
```

Path Parameters

Parameter	Description
agentId	Unique identifier of the host.

Request Parameters

Parameter	Description
serviceId	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/system-dump?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i
-X POST \
  -H 'Accept: application/json;charset=UTF-8' \
  -H 'NetWitness-Token: eyJ...AT' \
  -H 'Content-Type: application/x-www-form-urlencoded; charset=ISO-8859-1'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Note: System Dump Download is not supported in Relay Mode

Request Process Dump Download

This API initiates the download of the process dump to the Endpoint Server.

Process information are specified as a part of the request body.

```
POST /rest/api/host/{agentId}/download/process-dump?serviceId=<service-id>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/download/process-dump?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X POST \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/json' \
-d
'{"processId":5744,"eprocess":"0xFFFFE10DC62C6440","fileName":"spoolsvX.bat","path":"E\\Windows\\ReportServer\\PolicyDefinitions","hash":"687685b7531648c39fbb24fa81312b7fd2e3ece1bf1347b386f8725783767e5c","processCreateUtcTime":1670836387232}'
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Request Network Isolation

This API isolates the host with the specified agent ID from the network.

```
POST /rest/api/host/{agentId}/isolation?serviceId=<service-id>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X POST \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/json' \
-d
'{"allowDnsOnlyBySystem":false,"exclusions":[{"ip":"10.125.0.1","v4":true}],"comment":
"Found malicious"}'
```

HTTP request

```
POST /rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 103

{"allowDnsOnlyBySystem":false,"exclusions":[{"ip":"10.125.0.1","v4":true}],"comment":"Found malicious"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Update Network Isolation Exclusion List

This API updates the network isolation exclusion list for the host with the specified agent ID.

```
PATCH /rest/api/host/{agentId}/isolation?serviceId=<service-id>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X PATCH \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/json' \
-d
'{"allowDnsOnlyBySystem":false,"exclusions":[{"ip":"1.2.3.4","v4":true},{"ip":"10.125.0.1","v4":true}],comment:"Updating IP exclusions for network isolation"}
```

HTTP request

```
PATCH /rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 159
```

```
{"allowDnsOnlyBySystem":false,"exclusions":[{"ip":"1.2.3.4","v4":true},{"ip":"10.125.0.1","v4":true}],comment:"Updating IP exclusions for network isolation"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```

Release from Network Isolation

This API restores the network connection and removes IP addresses added to the exclusion list for the host with the specified agent ID.

```
DELETE /rest/api/host/{agentId}/isolation?serviceId=<service-id>
```

Path Parameters

Parameter	Description
<code>agentId</code>	Unique identifier of the host.

Request Parameters

Parameter	Description
<code>serviceId</code>	Service ID of the Endpoint Server to be connected.

Sample Request

```
$ curl 'https://api.netwitness.local/rest/api/host/B27DDED7-6FFA-A9D3-6577-3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8' -i -X DELETE \
-H 'Accept: application/json;charset=UTF-8' \
-H 'NetWitness-Token: eyJ...AT' \
-H 'Content-Type: application/json' \
-d '{"allowDnsOnlyBySystem":false,"exclusions":null,"comment":"Release from isolation"}'
```

HTTP request

```
DELETE /rest/api/host/B27DDED7-6FFA-A9D3-6577-
3DDE367B2820/isolation?serviceId=5f6e15bb-9384-4666-aa71-e5d134afd7d8 HTTP/1.1
Accept: application/json;charset=UTF-8
NetWitness-Token: eyJ...AT
Content-Type: application/json
Host: api.netwitness.local
Content-Length: 83
```

```
{"allowDnsOnlyBySystem":false,"exclusions":null,"comment":"Release from isolation"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Mon, 12 Dec 2022 09:13:06 GMT
Keep-Alive: timeout=60
Connection: keep-alive
```